LOWER TWEED RIVER DEPTHS AS AT JUNE-AUGUST 2008

NOTES: WARNINGS: Channel locations and riverbed conditions may change and caution should be used 1. Surveys are undertaken to monitor changes in the lower river shoals as part of the Tweed when navigating this river. River Entrance Sand Bypassing Project's environmental monitoring program. Riverbed contours show average depths in metres below Tweed River Hydro Datum 2. Tweed River Entrance conditions are provided separately on the Tweed River Entrance seabed maps. (approximately ISLW), not clearance depths. FINGAL OCEANPACIFIC Refer to Tweed River Entrance seabed maps SOUTHBANORA **LEGEND KEY** POINT J Ukerbagh Average Depths in metres Boat ramp below Tweed River Hydro Datum Boatharbour Waterline Ukerebagh 3 to 4 4 to 6 1000 6 to 8 8 to 10 >10 metres Survey information collected by the Gold Coast City Council during 25/06-27/08/2008, for the Tweed River Entrance TWEED RIVER ENTRANCE SAND BYPASSING PROJECT Sand Bypassing Project.

Department of Lands

The Tweed River Entrance Sand Bypassing Project is a joint project of

the New South Wales and Queensland Governments, with the support of

the Gold Coast City Council, and in conjunction with the Tweed Shire Council.

Queensland